



**Applications:**

1.71GHz-2.17GHz 08dBi ISM Band  
DCS1800 GSM1800 1.8GHz 2G  
PCS1900 GSM1900 1.9GHz  
PCS2000 GSM2000 3G 3.5G  
WiFi, CDMA, RFID, GSM  
Directional and multipoint applications  
Public Wireless Hotspot  
Wireless Video Systems

**Features :**

Superior performance  
Light weight  
Cable 1.5m  
Multiple options  
Durable UV-stable  
Can be installed for either  
vertical or horizontal polarization  
RoHS Compliant

**SPECIFICATIONS:**

**SPECIFICATIONS:**

**Applications:**

Frequency Range 1.71~2.17GHz
V.S.W.R ≤1.5
Return Loss ≥-14db
Antenna Type PCB patch array
Gain 08dBi
Polarization Vertical or Horizontal
Maximum Power 50W
Vertical Beam-with 75°
Horizontal Beam-with 38°
Impedance 50Ω
Connector RP SMA male/1.5m

**Mechanical Specifications:**

Size L150 x W90 x H30mm
Weight 245g
Wind Survival N/A
Radome Material ABS + UV resistance
Operating Temperature -40°C to +80°C
Clamps Multiple options
Mounting Multiple options