

Wireless LAN Access Point

IEEE 802.11g/b Compatible

IEEE 802.11g/b Wireless LAN Access Point

Acting as a bridge between the wired Ethernet and the 2.4GHz IEEE 802.11g/b wireless LAN, this wireless LAN access point can let your wireless LAN client stations access both the wired and the wireless network nodes.

WDS Bridge Mode (Repeater Mode)

The WDS (Wireless Distributed System) function lets this access point act as an wireless LAN access point and repeater at the same time.

Users can use this feature to build up a large wireless network in a large space like airports, hotels and schools ...etc. This feature is also useful when users want to bridge networks between buildings where it is impossible to deploy network cable connections between these buildings.

Station Mode (AP Client Mode)

By setting this access point into station mode and connecting to a network device's Ethernet port, it can let a network device that originally only supports wired Ethernet access the wireless LAN easily without changing any configuration.

Robust Wireless LAN Security

Except for the basic security control by using ESSID and 64/128 bit key length WEP encryption, this access point also supports the advanced security features, like MAC access control and hide ESSID. It provides a total solution for you to build up a secure wireless LAN network environment that can prevent from all kinds of hacker intrusion.

RP-SMA Detachable Antenna

This access point provides a standard RP-SMA antenna connector that can let you apply all kinds of high gain antennas. This can help you enlarge your wireless LAN coverage.

Web Configuration

You can configure this access point through the friendly Web user interface with a browser.



EW-7206APg

Main Features

- Wireless Signal Rate(With automatic fallback):
- 802.11g:54Mbps,48Mbps,36Mbps,24Mbps,18Mbps,12Mbps,9Mbps,6Mbps
- 802.11b:11Mbps,5.5Mbps,2Mbps,1Mbps
- Auto rate fallback in case of obstacles or interferences
- Supports 2.400~2.4835 GHz frequency band, 1~14 channels

- Provides 64/128 bit key length WEP data encryption
- Supports WPA / WPA2 security enhanced function
- Supports WDS (Wireless Distributed System) bridge mode
- Provide SSID broadcast disable function
- Provides station mode to act as a wireless LAN client station
- Supports roaming link integrity
- Supports authentication for wireless connectivity based on ESSID
- Provides MAC access control and MAC address filtering
- Provides DHCP server
- Provide system status by LEDs indicator.
- Supports Web-based configuration
- Firmware upgradeable via Web
- Compact-size design

Main Specification

Product	EW-7206APg
Standard	IEEE802.11b/g ,802.3,802.3u
Frequency	2.400~2.4835 GHz
LAN Port	10/100M UTP Port x 1
Antenna	RP-SMA Detachable Antenna x 1
Transmit Power	18 dBm
Power Supply	12V DC, 0.5A Power Adaptor
Dimension	30(H)*127(W)*96(D) mm
Operation Temperature	10~40 °C
Operation Humidity	10~90% (Non-Condensing)
Certification	FCC , CE
RAM	8MB SDRAM
Flash	2 MB NOR Flash